

4x4 PRODUCT ADVICE TTP904H

Description:	Heavy Duty Tree Protector Strap (green) <i>Serious range.</i>
Application:	To protect the tree when using it to winch from.
Ratings:	8,000Kg Recovery Load Limit R.L.L.® 12,000Kg Minimum Breaking Strength. MBS
Safety Factor:	1.5 to 1 Factor of Safety (F of S)
Standard:	Product Safety and Information Standard™ JSF (AUST) 2007™
Size:	90mm / 4 metre
Part #:	TTP904H

Recovery Load Limit R.L.L.®. The maximum load that may be applied to equipment used in the recovery role.

Minimum Breaking Strength. MBS. The minimum load necessary to cause equipment to fail or fracture.

Factor of Safety. F of S. A number divided into the minimum breaking strength to determine the recovery load limit.

Safety Warning: *Use of this product and participation involves inherent risks of injury or death.*

This product must not be used for any lifting purposes. Inspect complete strap before each use. Protect webbing strap from abrasion and sharp edges. Do not use the strap if cut or damaged. Do not tie knots in webbing strap. Only use the correct strap for its designed purpose. Evaluate each situation and use the correct rated product that will best suit. Do not attach any strap to a standard tow ball, standard vehicle tie-down point or a standard nudge or bull bar. Attach only to a suitable rated recovery point or device. Refer to manufacturer's recommendations. Always follow our product instructions and if in doubt, ask an expert. Driver Trainers are such people, with full knowledge and expertise advice. Keep all persons clear while recovery is in progress, at least the same distance away from the vehicles as the length of the strap is, in the opposite direction. Use a blanket, towel or our specially designed Safety Weight Blanket and place it over the middle of the strap to absorb the re-coil action should any equipment fail. Outside parameters can reduce the life and capacity of the strap. Strength and characteristics are reduced when wet. Keep away from any chemicals and out of direct sunlight. Clean dirt, sand, etc from the strap with water and mild detergent if required, and allow to dry prior to storing in our specially designed recovery bags.

Note: The user of this strap assumes all risk and liability for its handling and use.

TREE PROTECTOR STRAPS: Designed use.

To be used around the base to protect the tree from abrasion when used as an anchor to winch from. Use **only** a rated Bow Shackle, 4.7 Tonne minimum to attach the Off Road Block (Pulley Block) to the eyes of the Tree Trunk Protector. To maximise the capacity of a Tree Trunk Protector the angle at which the two eyes (ends) meet, must be as small as possible. The bigger the diameter of the tree the longer the strap needs to be.

NOTE: We recommend the use of our unique *Four Wheel Drive Recovery Safety Strap* be used in each recovery situation. Use our specially designed *Recovery Bags* for safe storage. Remember, if joining straps of a different rating, then treat the lowest rating as the entire strap rating. Do not use a shackle to join straps together. Always wear safety gloves.

Please refer to our 4x4 Force Calculation document for product selection.

Phone: 02 9894 1899
Fax: 02 9894 1811
Email: info@juststraps.com.au
Web: www.juststraps.com.au



© Just Straps Product TTP904H



Just strap it and GO!®

Copyright © 2007